



	<p><b>3/4" Short Base</b> SB25G Base section for embedment in concrete.</p> <p><b>5' Short Base (not shown)</b> SB25G5 Base section for embedment in concrete.</p> <p><b>3/4" Hinged Short Base</b> SBH25G* Base section for embedment in concrete. Hinged connection to bottom</p>		<p><b>Concrete Base Plate</b> BPC25G* For use with pier pin embedded in concrete.</p> <p><b>Pier Pin</b> 3/4X12PP Must be ordered separately.</p>
	<p>(Left) <b>Standard 25G Section</b> 25G Standard 10' section with seven bays of bracing and swaged, double-bolted connections.</p> <p><b>7' 25G Section</b> 25G7 (not shown) Same design and materials as 10' section, but only 7' long to allow UPS shipping.</p> <p>(Left Center) <b>10' Insulator Section</b> 25RG*</p> <p>(Right Center) <b>Anti-Climb Section</b> 25ACL Used as bottom section to help prevent unauthorized climbers.</p> <p><b>Anti-Climb Panels</b> 25ACL3 (not shown) Three anti-climb panels to bolt to existing standard tower section.</p> <p>(Right) <b>Tapered Base</b> 25TGA* Can be used with RACAL DECCA A4197L base insulator or with 3/4X12PP.</p>		<p><b>Single Drive-In Base</b> SDB25G* To be driven directly into ground.</p>
	<p><b>Base Plate</b> BP25G For use with drive rods. Tower must be guyed or bracketed.</p> <p><b>2' Drive Rods</b> DR25G* Set of 3 drive rods for use with BP25G base plate.</p> <p><b>Drive Tool</b> DT25 For DR25G/BP25G installation. Slips over top of drive rod to protect from damage during installation.</p>		<p><b>Peak Roof Mount</b> PR25G* Adjustable hinged feet conform to nearly any roof pitch. Bolts to roof surface.</p>
	<p><b>Flat Roof Mount</b> FR25G* Bolts directly to flat roof surface</p>		<p><b>Hinged Base Plate</b> BPH25G* Bolts to concrete. Hinged to allow tower to be rotated up from base during installation.</p> <p><b>Base Bolts</b> 1/2X12BB Must be ordered separately.</p>
	<p><b>90 Degree Joints</b> 2590MM 2590FM 2590FF Unique 90 degree joints allows the connection of 25G sections for a variety of purposes. Popular in theatrical staging and overhead lighting. Joint styles include (2590MM) both ends swaged, (2590FF) both ends open, and (2590FM) a combination one end swaged the other open. Joints are not drilled where they slip fit to 25G sections. Can be filed drilled or custom connected to meet particular needs.</p>		

\* Towers mounted on these bases must be bracketed or guyed at all times. Temporary steel guying may also be necessary during installation and dismantling.